Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1AV3130A **SIMOTICS GP - 132 S - IM B14 - 2p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_l/I_N	M_A/M_N T_l/T_N	M_K/M_N T_B/T_N	IE-CL
400	Δ	50	4.78	-/-	9.00	2950	15.5	89.4	89.1	87.7	0.86	0.80	0.67	10.2	2.9	4.4	IE3
690	Y	50	4.78	-/-	5.20	2950	15.5	89.4	89.1	87.7	0.86	0.80	0.67	10.2	2.9	4.4	IE3
460	Δ	60	5.48	-/-	9.00	3545	14.8	88.8	88.6	87.2	0.86	0.80	0.70	11.4	3.0	4.6	IE2
460	Δ	60	5.50	-/-	8.90	3550	14.8	89.5	89.0	87.0	0.87	0.82	0.71	11.1	3.0	4.6	IE3
IM B14 / IM 3601			FS 132 S	43 kg	IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +55 °C / 1,000 m

Locked rotor time (hot / cold) : 0 s | 0 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	68.0 / 80.0 dB(A) 2)	72.0 / 84.0 dB(A) 2)	External earthing terminal	No
Moment of inertia	0.0168 kg m²		Vibration severity grade	A
Bearing DE | NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS	document type: datasheet	document status: released		customer
	title: **1LE1003-1CA03-4KB4-Z** **F76+L20+N07**	document number		
		rev.: 01	creation date: 2021-06-08 09:51	language: en / Page: 1/2

© Siemens AG 2021

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1AV3130A **SIMOTICS GP - 132 S - IM B14 - 2p**

Special design

F76	Metal external fan	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced
L20	Locating bearing, DE		

Notes:

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS	document type: datasheet		document status: released		customer
	title: 1LE1003-1CA03-4KB4-Z F76+L20+N07		document number		
© Siemens AG 2021		rev.: 01	creation date: 2021-06-08 09:51	language: en	Page: 2/2