

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3130B

SIMOTICS GP - 132 S - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
415	Δ	50	5.50	-/-	10.20	1470	35.5	89.6	90.1	89.5	0.84	0.79	0.69	7.2	2.1	3.4	IE3
480	Δ	60	6.30	-/-	10.10	1770	34.0	89.5	89.8	89.1	0.84	0.80	0.71	7.3	2.3	3.4	IE2
480	Δ	60	5.50	-/-	8.90	1775	29.5	89.5	89.4	88.2	0.83	0.78	0.68	8.2	2.6	3.9	IE2
IM B35 / IM 2001		FS 132 S		64 kg		IP56		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 15.3 s | 20.4 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64.0 / 76.0 dB(A) ²⁾	68.0 / 80.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0340 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1003-1CB03-5JB4-Z B02+H03+H22+Q02+Y82			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-05-28 10:04	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3130B

SIMOTICS GP - 132 S - IM B35 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Q02	Anti-condensation heating for 230 V (2 terminals)
H03	Condensation drain holes in end shield	Y82	Auxiliary name plate with customer data
H22	IP 56 degree of protection		

Additional information:

Space heaters

Technical data: 1-phase, 230 V 50W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1003-1CB03-5JB4-Z			document number				
© Siemens AG 2021	B02+H03+H22+Q02+Y82			rev. 01	creation date 2021-05-28 10:04	language en	Page 2/2	