



**SIMOTICS GP - 132 M - IM B5 - 4p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

[illegible]

|                                                                                        |                                |                                |                                 |                                                    |
|----------------------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                   | 64 / 76 dB(A) <sup>2) 3)</sup> | 68 / 80 dB(A) <sup>2) 3)</sup> | Vibration severity grade        | A                                                  |
| Moment of inertia                                                                      | 0.0334 kg m²                   |                                | Thermal class                   | F                                                  |
| Bearing DE   NDE                                                                       | 6208 2Z C3                     | 6208 2Z C3                     | Duty type                       | S1                                                 |
| <b>bearing lifetime</b>                                                                |                                |                                | Direction of rotation           | bidirectional                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation<br>50 60Hz <sup>1)</sup> | 40000 h                        | 32000 h                        | Frame material                  | aluminum                                           |
| Regreasing device                                                                      | No                             |                                | Net weight of the motor (IM B3) | 61 kg                                              |
| Grease nipple                                                                          | -/-                            |                                | Coating (paint finish)          | Standard paint finish C2                           |
| Type of bearing                                                                        | Preloaded bearing DE           |                                | Color, paint shade              | RAL7030                                            |
| Condensate drainage holes                                                              | No                             |                                | Motor protection                | (B) 3 PTC thermistors - for tripping (2 terminals) |
| External earthing terminal                                                             | No                             |                                | Method of cooling               | IC411 - self ventilated, surface cooled            |

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 6 mm²               |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 11 mm - 21 mm       |
| Type of terminal box     | TB1 H00   | Cable entry                    | 2xM32x1,5-1xM16x1,5 |
| Contact screw thread     | M4        | Cable gland                    | 3 plugs             |

Notes:

|                                                    |                                           |                                                                  |
|----------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| $I_r/I_n$ = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| $M_r/M_n$ = locked rotor torque / torque nominal   | 2) at rated power / at full load          |                                                                  |
| $M_b/M_n$ = break down torque / nominal torque     |                                           |                                                                  |

|                                                                                    |                               |                               |             |                                                                                                              |                             |                                                                                                                         |             |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------|-------------|
| responsible dep.<br>DI MC LVM                                                      | technical reference           | created by<br>DT Configurator | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                             | <a href="#">Link documents</a><br> |             |
|  | document type<br>datasheet    |                               |             | document status<br>released                                                                                  |                             |                                    |             |
|                                                                                    | title<br>1LE1003-1CB23-5FB4-Z |                               |             | document number                                                                                              |                             |                                                                                                                         |             |
| © Siemens AG 2023                                                                  | F01+F12+Q02                   |                               |             | rev.<br>935                                                                                                  | creation date<br>2023-02-01 | language<br>en                                                                                                          | Page<br>1/2 |



**SIMOTICS GP - 132 M - IM B5 - 4p**

|     |                                         |     |                                                   |
|-----|-----------------------------------------|-----|---------------------------------------------------|
| F01 | Mounting of holding brake               | Q02 | Anti-condensation heating for 230 V (2 terminals) |
| F12 | Brake supply voltage 400 V AC, 50/60 Hz |     |                                                   |

Space heaters

Brake:

|              |           |                    |                           |
|--------------|-----------|--------------------|---------------------------|
| Description: | BFK458-16 | Current:           | .31 A                     |
| Voltage:     | AC 400 V  | Moment of inertia: | 0.001500 kgm <sup>2</sup> |

|                                                                                    |                               |                               |             |                                                                                                              |                                                                                       |                                |             |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------------|-------------|
| responsible dep.<br>DI MC LVM                                                      | technical reference           | created by<br>DT Configurator | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                                                                                       | <a href="#">Link documents</a> |             |
|  | document type<br>datasheet    | document status<br>released   |             |                                                                                                              |  |                                |             |
|                                                                                    | title<br>1LE1003-1CB23-5FB4-Z |                               |             |                                                                                                              |                                                                                       |                                |             |
| © Siemens AG 2023                                                                  | F01+F12+Q02                   | rev.<br>935                   |             | creation date<br>2023-02-01                                                                                  |                                                                                       | language<br>en                 | Page<br>2/2 |