

SIMOTICS GP - 132 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 155(F)																	
440	Y	60	8.60	-/-	15.60	1765	46.5	89.5	90.0	89.4	0.81	0.76	0.65	8.8	3.0	3.8	IE2
255	Δ	60	7.50	-/-	23.50	1770	40.5	91.7	91.6	90.6	0.79	0.73	0.61	9.8	3.4	4.3	IE3
220	Δ	50	7.50	-/-	27.00	1465	49.0	90.4	90.7	90.4	0.80	0.74	0.63	8.5	3.0	3.8	IE3
IM B3 / IM 1001			FS 132 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -30 °C - + °C / 1,000 m									Locked rotor time (hot / cold) : 14.8 s 20.1 s								

Sound level (SPL / SWL) at 50Hz 60Hz	72 / 80 dB(A) ^{2) 3)}	68 / 76 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0334 kg m²		Thermal class	F
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	61 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC418 - without fan and without housing fan

Terminal box position	top	Max. cross-sectional area	6 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_{Lr}/I_{Ln} = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_{rn} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_{bn} = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE1003-1CB29-0AA4-Z			document number			
© Siemens AG 2023	D04+F90+H08+M1C+N03			rev. 943	creation date 2023-06-22	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3132B

SIMOTICS GP - 132 M - IM B3 - 4p

Special design

D04	Minimum ambient temperature -30°C	M1C	440 VY, 60-Hz power
F90	Without external fan and without external fan cover	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
H08	Terminal box at the NDE		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1003-1CB29-0AA4-Z				document number
© Siemens AG 2023				rev. 943	creation date 2023-06-22
				language en	Page 2/2

