

SIMOTICS GP - 132 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	11.00	-/-	38.00	1470	71.0	91.4	91.9	91.5	0.80	0.75	0.63	7.7	2.6	3.6	IE3
400	Y	50	11.00	-/-	21.50	1470	71.0	91.4	91.9	91.5	0.80	0.75	0.63	7.7	2.6	3.6	IE3
460	Y	60	12.60	-/-	21.00	1765	68.0	92.4	92.9	92.6	0.82	0.77	0.67	7.9	2.7	3.6	IE3
460	Y	60	11.00	-/-	19.00	1775	59.0	92.4	92.6	91.8	0.79	0.73	0.62	8.7	3.1	4.1	IE3
IM B3 / IM 1001			FS 132 M		81 kq		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Locked rotor time (hot / cold) : 15.8 s | 23.5 s

Sound level (SPL / SWL) at 50Hz 60Hz	69.0 / 73.0 dB(A) ²⁾	69.0 / 73.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0490 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(K) 1 Pt1000 resistance thermometer(2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	6.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1003-1CB62-2AK4-Z						
	F01+F70+G11+M10			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-21 10:59	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3136B

SIMOTICS GP - 132 M - IM B3 - 4p

Special design

F01	Mounting a brake	G11	Rotary pulse encoder Sendix 5020 (HTL)
F70	Mounting of separately driven fan	M10	Additional rating plate, loose

Additional information:

Brake:

Description:		Current:	A
Voltage:	V	Moment of inertia:	Nm

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

	document type datasheet	document status released		customer	
	title 1LE1003-1CB62-2AK4-Z F01+F70+G11+M10	document number			
© Siemens AG 2021		rev. 01	creation date 2021-04-21 10:59	language en	Page 2/2