

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3130C

SIMOTICS GP - 132 S - IM B5 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	3.00	-/-	6.90	975	29.5	85.6	85.8	84.3	0.73	0.65	0.51	6.6	2.3	3.2	IE3
690	Y	50	3.00	-/-	4.00	975	29.5	85.6	85.8	84.3	0.73	0.65	0.51	6.6	2.3	3.2	IE3
IM B5 / IM 3001			FS 132 S		42 kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 16.7 s 22 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 73 dB(A) ²⁾	69 / 73 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0340 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	No		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1003-1CC03-4FB4-Z		document number			
© Siemens AG 2021		F01+F12+F70+G11+N03+R11		rev.	creation date	language	Page
				01	2021-08-06 11:22	en	1/2

SIMOTICS GP - 132 S - IM B5 - 6p

Special design

F01	Mounting a brake	G11	Rotary pulse encoder Sendix 5020 (HTL)
F12	Brake supply voltage 400 V AC, 50/60 Hz	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
F70	Mounting of separately driven fan	R11	Terminal box rotated through 90°, cable entry from NDE

Additional information:

Brake:

Description:	BFK458-16	Current:	.31 A
Voltage:	AC 400 V	Moment of inertia:	0.001500 kgm ²

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1003-1CC03-4FB4-Z			document number				
© Siemens AG 2021	F01+F12+F70+G11+N03+R11			rev. 01	creation date 2021-08-06 11:22	language en	Page 2/2	