

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3132D

SIMOTICS GP - 132 M - IM B5 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 180(H) to 180(H)																	
220	Δ	50	3.00	-/-	13.10	725	39.5	83.5	83.8	82.2	0.72	0.64	0.51	5.2	2.0	2.5	IE3
380	Y	50	3.00	-/-	7.60	725	39.5	83.5	83.8	82.2	0.72	0.64	0.51	5.2	2.0	2.5	IE3
IM B5 / IM 3001			FS 132 M			IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - + °C / 1,000 m									Locked rotor time (hot / cold) : 26.1 s 35.1 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64 / 77 dB(A) ²⁾	67 / 80 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0610 kg m ²		Thermal class	H
Bearing DE NDE	6208 Z C3	6208 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz Lubricants	40000 h	32000 h	Frame material	aluminum
Regreasing device	No		Net weight of the motor (IM B3)	58 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	No		Motor protection	(A) without (Standard)
External earthing terminal	No		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-1CD22-1FA4-Z						
© Siemens AG 2022	N11			rev.	creation date	language	Page
				01	2022-02-04	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3132D

SIMOTICS GP - 132 M - IM B5 - 8p

Special design

N11 Temperature class 180(H), and coolant temperature max. 60°C

Notes:

responsible dep.
DI MC LVM

technical reference

created by
DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type
datasheet

title
1LE1003-1CD22-1FA4-Z
N11

document status
released

document number

