## Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type: 1AV3162A

SIMOTICS GP - 160 M - IM B5 - 2p

Client order no.

Item-No.

Consignment no.

Project

Remarks

Safe Area

Safe Area
| Electrical data -/-

Literatura da di																	
U	Δ/Υ	f	Р	Р	ı	n	М	η 3)		cosφ <sup>3)</sup>		$I_A/I_N$	M <sub>A</sub> /M <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub>	IE-CL		
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	$I_I/I_N$	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>	
					D	OL duty (S1)	- 155(F	to 130	(B)								
380	Δ	50	11.00	-/-	20.50	2945	35.5	91.2	91.4	90.6	0.89	0.86	0.79	8.3	2.5	3.5	IE3
660	Υ	50	11.00	-/-	11.90	2945	35.5	91.2	91.4	90.6	0.89	0.86	0.79	8.3	2.5	3.5	IE3
440	Δ	60	12.60	-/-	20.00	3540	34.0	91.0	90.9	89.5	0.90	0.87	0.81	8.4	2.5	3.5	IE3
440	Δ	60	11.00	-/-	18.00	3555	29.5	91.0	90.4	88.4	0.88	0.85	0.77	9.5	2.9	4.0	IE3
IM B5 / IM 3001			FS 160 M			IP55	UKCA	IEC/EN	60034		IEC, DIN, IS	O, VDE, EN	I				

Environmental conditions: -20 °C - +40 °C / 1000 m Locked rotor time (hot / cold): 21.3 s | 29.7 s

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	77 / 85 dB(A) <sup>2) 3)</sup>	82 / 90 dB(A) 2) 3)	Vibration severity grade	Α		
Moment of inertia	0.0370	) kg m²	Thermal class	F		
Bearing DE   NDE	6209 2Z C3	6209 2Z C3	Duty type	S1		
bearing lifetime			Direction of rotation	bidirectional		
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>	40000 h	32000 h	Frame material	aluminum		
Regreasing device	Witho	out	Net weight of the motor (IM B3)	70 kg		
Grease nipple	-,	I-	Coating (paint finish)	Standard paint finish C2		
Type of bearing	Locating b	earing NDE	Color, paint shade	RAL7030		
Condensate drainage holes	With	hout	Motor protection	(A) without (Standard)		
External earthing terminal	With	nout	Method of cooling	IC411 - self ventilated, surface cooled		

## Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from to	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

 $I_A/I_N = locked rotor current / current nominal$   $M_A/M_N = locked rotor torque / torque nominal$ 

1) L<sub>10mh</sub> according to DIN ISO 281 10/2010 2) at rated power / at full load 3) Value is valid only for DOL operation with motor design IC411

 $M_k/M_N$  = break down torque / nominal torque

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference			Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			Link documents		
	Document type					tatus	h e a		
SIEMENS	Technical data sheet								
<b>PIEIMIEIA2</b>	Document title				Document r	number			
	1LE1003-1DA23-3FA4					TDS-240417-154221		IN WEST AND TO	
Restricted					Revision	Creation date	Language	Page	
© Innomotics 2024					AA	2024-04-17	en	1/1	