

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3162B

SIMOTICS GP - 160 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	11.00	-/-	37.00	1470	71.0	91.4	91.9	91.9	0.82	0.76	0.65	8.0	2.5	3.5	IE3
400	Y	50	11.00	-/-	21.00	1470	71.0	91.4	91.9	91.9	0.82	0.76	0.65	8.0	2.5	3.5	IE3
460	Y	60	12.60	-/-	20.50	1765	68.0	92.4	92.9	92.6	0.83	0.78	0.68	8.1	3.3	3.5	IE3
460	Y	60	11.00	-/-	18.40	1775	59.0	92.4	92.6	92.0	0.81	0.75	0.63	9.0	3.8	4.0	IE3

IM B5 / IM 3001		FS 160 M		IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN						
-----------------	--	----------	--	------	--	--------------	------------------------	--	--	--	--	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 25.9 s | 33.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 79 dB(A) ²⁾	75 / 79 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0583 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	78 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC416 - separately ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1003-1DB22-2FA4-Z F01+F11+F70			
© Siemens AG 2021		rev.	creation date	language Page
		01	2021-10-23 13:42	en 1/2

SIMOTICS GP - 160 M - IM B5 - 4p

F01	Mounting a brake	F70	Mounting of separately driven fan
F11	Brake supply voltage, 230 V AC, 50/60 Hz		

Brake:

Description:	BFK458-20	Current:	.5 A
Voltage:	AC 230 V	Moment of inertia:	0.007300 kgm ²

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

document type	document status		customer	
datasheet	released			
title	document number			
1LE1003-1DB22-2FA4-Z				
F01+F11+F70	rev.	creation date	language	Page
	01	2021-10-23 13:42	en	2/2