

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3162B

SIMOTICS GP - 160 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _i /I _N	T _i /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	11.00	-/-	22.50	1470	71.0	91.4	91.9	91.9	0.82	0.76	0.65	8.0	2.5	3.5	IE3
660	Y	50	11.00	-/-	12.80	1470	71.0	91.4	91.9	91.9	0.82	0.76	0.65	8.0	2.5	3.5	IE3
440	Δ	60	12.60	-/-	21.50	1765	68.0	92.4	92.9	92.6	0.83	0.78	0.68	8.1	3.3	3.5	IE3
440	Δ	60	11.00	-/-	19.30	1775	59.0	92.4	92.6	92.0	0.81	0.75	0.63	9.0	3.8	4.0	IE3
IM B5 / IM 3001			FS 160 M				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 26.5 s 34.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65 / 77 dB(A) ^{2) 3)}	69 / 81 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0583 kg m ²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
$L_{10mh} F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	78 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC416 - separately ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-1DB23-3FA4-Z						
© Siemens AG 2022	F70+G11			rev.	creation date	language	Page
				929	2022-11-03	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3162B

SIMOTICS GP - 160 M - IM B5 - 4p

Special design

F70 Mounting of separately driven fan G11 Rotary pulse encoder Sendix 5020 (HTL)

Notes:

responsible dep.
DI MC LVM

technical reference

created by
DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type
datasheet

title
1LE1003-1DB23-3FA4-Z
F70+G11

document status
released

document number

