

SIMOTICS GP - 160 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

[illegible]

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 75 dB(A) ^{2) 3)}	70 / 75 dB(A) ^{2) 3)}	External earthing terminal	Without
Moment of inertia	0.0583 kg m²		Vibration severity grade	A
Bearing DE NDE	6209 Z C3	6209 Z C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g 8000 h		Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	78 kg
Regreasing device	With		Coating (paint finish)	Standard paint finish C2
Grease nipple	M8x1 DIN 71412		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_L/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-1DB23-4FA4-Z						
	L23+Y82			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-05-22	en	1/2

SIMOTICS GP - 160 M - IM B5 - 4p

Special design

L23	Regreasing system	Y82	Auxiliary name plate with customer data
-----	-------------------	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1003-1DB23-4FA4-Z			document number			
© Siemens AG 2023	L23+Y82			rev. 943	creation date 2023-05-22	language en	Page 2/2