

GP motor type: 1AV3162B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) aluminum enclosure Premium Efficiency IE3, 4-pole * size 160M, * 11 kW (50 Hz) 12.6 kW (60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 400 VD/690 VY * 3 AC 60 Hz 460 VD IM V 1 without canopy, flange: FF300 (A350) 3 PTC thermistors for disconnection (2 terminals) Terminal box at top B12=Seaworthy packaging for non-overseas customers D34=China Energy Efficiency label F74=Sheet metal fan cover H00=Canopy P02=Next smaller standard flange: FF265 (A300) S03=Special paint finish, sea air resistant Y53=Paint finish in other standard RAL colors (for selection see catalog) RAL... Y58=Non-standard cylindrical shaft extension, DE (DE)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

