



**SIMOTICS GP - 160 M - IM B5 - 6p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U                                                    | Δ / Y | f    | P        | P    | I     | n       | M    | η <sup>3)</sup> |                                                |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|------------------------------------------------------|-------|------|----------|------|-------|---------|------|-----------------|------------------------------------------------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                  |       | [Hz] | [kW]     | [hp] | [A]   | [1/min] | [Nm] | 4/4             | 3/4                                            | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| DOL duty (S1) - 155(F) to 130(B)                     |       |      |          |      |       |         |      |                 |                                                |                        |                    |      |      |                                |                                |                                |       |
| 380                                                  | Δ     | 50   | 7.50     | -/-  | 15.80 | 985     | 73.0 | 89.1            | 89.7                                           | 89.0                   | 0.81               | 0.76 | 0.65 | 7.9                            | 2.3                            | 3.2                            | IE3   |
| 660                                                  | Y     | 50   | 7.50     | -/-  | 9.10  | 985     | 73.0 | 89.1            | 89.7                                           | 89.0                   | 0.81               | 0.76 | 0.65 | 7.9                            | 2.3                            | 3.2                            | IE3   |
|                                                      |       |      |          |      |       |         |      |                 |                                                |                        |                    |      |      |                                |                                |                                |       |
|                                                      |       |      |          |      |       |         |      |                 |                                                |                        |                    |      |      |                                |                                |                                |       |
| IM B5 / IM 3001                                      |       |      | FS 160 M |      |       | IP55    | UKCA | IEC/EN 60034    |                                                | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1,000 m |       |      |          |      |       |         |      |                 | Locked rotor time (hot / cold) : 13 s   17.2 s |                        |                    |      |      |                                |                                |                                |       |

|                                                                                        |                                |                                |                                 |                                                    |
|----------------------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                   | 67 / 79 dB(A) <sup>2) 3)</sup> | 70 / 82 dB(A) <sup>2) 3)</sup> | Vibration severity grade        | A                                                  |
| Moment of inertia                                                                      | 0.1320 kg m²                   |                                | Thermal class                   | F                                                  |
| Bearing DE   NDE                                                                       | 6209 2Z C3                     | 6209 2Z C3                     | Duty type                       | S1                                                 |
| <b>bearing lifetime</b>                                                                |                                |                                | Direction of rotation           | bidirectional                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation<br>50 60Hz <sup>1)</sup> | 40000 h                        | 32000 h                        | Frame material                  | aluminum                                           |
| Regreasing device                                                                      | Without                        |                                | Net weight of the motor (IM B3) | 95 kg                                              |
| Grease nipple                                                                          | -/-                            |                                | Coating (paint finish)          | Standard paint finish C2                           |
| Type of bearing                                                                        | Locating bearing NDE           |                                | Color, paint shade              | RAL7030                                            |
| Condensate drainage holes                                                              | Without                        |                                | Motor protection                | (B) 3 PTC thermistors - for tripping (2 terminals) |
| External earthing terminal                                                             | Without                        |                                | Method of cooling               | IC411 - self ventilated, surface cooled            |

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 16 mm²              |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 19 mm - 28 mm       |
| Type of terminal box     | TB1 J00   | Cable entry                    | 2xM40x1,5-1xM16x1,5 |
| Contact screw thread     | M5        | Cable gland                    | 3 plugs             |

**Notes:**

|                                                          |                                           |                                                                  |
|----------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| $I_{Lr}/I_{Ln}$ = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| $M_r/M_{rn}$ = locked rotor torque / torque nominal      | 2) at rated power / at full load          |                                                                  |
| $M_b/M_{bn}$ = break down torque / nominal torque        |                                           |                                                                  |

|                            |                             |                   |             |                                                                                                              |                             |                                                                                       |             |
|----------------------------|-----------------------------|-------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------|-------------|
| responsible dep.<br>IN LVM | technical reference         | created by<br>SPC | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                             | <a href="#">Link documents</a>                                                        |             |
| SIEMENS                    | document type<br>datasheet  |                   |             | document status<br>released                                                                                  |                             |  |             |
|                            | title<br>1LE1003-1DC23-3FB4 |                   |             | document number                                                                                              |                             |                                                                                       |             |
| © Siemens AG 2023          |                             |                   |             | rev.<br>943                                                                                                  | creation date<br>2023-08-08 | language<br>en                                                                        | Page<br>1/1 |