

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3164D

SIMOTICS GP - 160 L - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	6.15	-/-	16.60	730	80.5	87.9	87.9	87.0	0.61	0.53	0.40	4.6	1.9	2.3	IE3
460	Δ	60	7.05	-/-	15.70	880	76.5	90.1	90.2	89.7	0.62	0.55	0.42	4.8	2.1	2.3	IE3
460	Δ	60	7.27	-/-	16.10	880	78.9	89.5	89.7	88.7	0.63	0.56	0.45	4.4	2.1	2.3	IE3
IM B3 / IM 1001		FS 160 L		110 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +60 °C / 1,000 m

Locked rotor time (hot / cold) : 67.5 s | 103 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 78.0 dB(A) ²⁾	66.0 / 79.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.1160 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 2Z C3	6309 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	1 gland, 1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1003-1DD40-4AA4-Z H00+H01+H02+N08+R15+S02			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-04-21 10:45	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3164D

SIMOTICS GP - 160 L - IM B3 - 8p

Special design

H00	Canopy	N08	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 60°C, power reduced
H01	Bolted on mounting feet (instead of cast)	R15	One metal cable gland
H02	Vibration-proof version	S02	Special paint finish C3

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1003-1DD40-4AA4-Z	document number					
© Siemens AG 2021	H00+H01+H02+N08+R15+S02		rev. 01	creation date 2021-04-21 10:45	language en	Page 2/2	