

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3182A

SIMOTICS GP - 180 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	60	22.00	-/-	41.00	3560	59.0	91.7	91.8	90.9	0.89	0.89	0.80	9.0	2.5	3.9	IE3
660	Y	60	22.00	-/-	23.50	3560	59.0	91.7	91.8	90.9	0.89	0.89	0.80	9.0	2.5	3.9	IE3
IM B3 / IM 1001			FS 180 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 19.6 s 29.9 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 80 dB(A) ²⁾	78 / 85 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0800 kg m ²		Thermal class	F
Bearing DE NDE	6210 Z C3	6210 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	122 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE1003-1EA29-0AB4			document number			
© Siemens AG 2022	M2B			rev. 01	creation date 2022-02-14	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3182A

SIMOTICS GP - 180 M - IM B3 - 2p

Special design

M2B 380 VD/660 VY for 60 Hz, 50-Hz power

Notes:

responsible dep.
DI MC LVM

technical reference

created by
DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type
datasheet

title
1LE1003-1EA29-0AB4
M2B

document status
released

document number

