

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3182B SIMOTICS GP - 180 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	18.50	-/-	35.00	1470	120.0	92.6	93.1	92.9	0.82	0.77	0.68	7.2	2.5	3.3	IE3
690	Y	50	18.50	-/-	20.50	1470	120.0	92.6	93.1	92.9	0.82	0.77	0.68	7.2	2.5	3.3	IE3
460	Δ	60	21.30	-/-	35.00	1770	115.0	92.4	92.8	92.4	0.83	0.79	0.70	7.2	2.4	3.2	IE2
460	Δ	60	18.50	-/-	30.50	1775	100.0	93.6	93.6	92.7	0.81	0.74	0.62	8.7	2.6	3.8	IE3
IM B3 / IM 1001		FS 180 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 27.8 s 40.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 73 dB(A) ²⁾	68 / 75 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.1300 kg m ²		Thermal class	F
Bearing DE NDE	6210 Z C3	6210 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min ¹⁾ for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	134 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_B/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-1EB23-4AA4						
© Siemens AG 2022				rev.	creation date	language	Page
				01	2022-02-12	en	1/1