

SIMOTICS GP - 180 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

[illegible]

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 73 dB(A) ^{2) 3)}	68 / 75 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1300 kg m²		Thermal class	F
Bearing DE NDE	6210 2Z C3	6210 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	134 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	Without		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

I_{lr}/I_n = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_n = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_n = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-1EB23-4FB4-Z						
	B02+F01+F12+F70+G04			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-08-30	en	1/2

SIMOTICS GP - 180 M - IM B5 - 4p

B02	Acceptance test certificate 3.1 acc. to EN 10204	F70	Mounting of separately driven fan
F01	Mounting of holding brake	G04	Mounted rotary pulse encoder LL 861 900 220
F12	Brake supply voltage 400 V AC, 50/60 Hz		

Brake:

Description:	BFK458-20	Current:	A
Voltage:	AC 400 V	Moment of inertia:	kgm ²

--

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet	document status released					
	title 1LE1003-1EB23-4FB4-Z						
© Siemens AG 2023	B02+F01+F12+F70+G04	rev. 943	creation date 2023-08-30		language en	Page 2/2	