

SIMOTICS GP - 200 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	55.00	1470	195.0	93.6	94.0	93.7	0.84	0.80	0.71	7.3	2.6	3.1	IE3
690	Y	50	30.00	-/-	32.00	1470	195.0	93.6	94.0	93.7	0.84	0.80	0.71	7.3	2.6	3.1	IE3
460	Δ	60	34.50	-/-	55.00	1770	186.0	93.0	93.3	92.9	0.85	0.81	0.73	7.3	2.4	3.0	IE2
460	Δ	60	30.00	-/-	48.00	1778	161.0	94.1	94.2	93.6	0.83	0.79	0.70	8.8	2.6	3.5	IE3
IM B3 / IM 1001			FS 200 L			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 29.4 s | 45 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65 / 72 dB(A) ^{2) 3)}	67 / 74 dB(A) ^{2) 3)}	External earthing terminal	Without
Moment of inertia	0.2400 kg m²		Vibration severity grade	A
Bearing DE NDE	6212 C3	6212 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} , F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	15 g 15 g 8000 h		Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	189 kg
Regreasing device	With		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L00	Cable entry	2xM50x1,5-1xM16x1,5
Contact screw thread	M6	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-2AB53-4AB4-Z						
	F75+L23			rev.	creation date	language	Page
© INNOMOTICS 2024				953	2024-01-11	en	1/2

SIMOTICS GP - 200 L - IM B3 - 4p

Special design

F75	Fan cowl for the textile industry	L23	Regreasing system
-----	-----------------------------------	-----	-------------------

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1003-2AB53-4AB4-Z						
	F75+L23			rev.	creation date	language	Page
© INNOMOTICS 2024				953	2024-01-11	en	2/2