

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV4163A

SIMOTICS GP - 160 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
380	Δ	50	15.00	-/-	27.00	2955	48.5	93.3	93.5	92.9	0.90	0.87	0.80	9.0	3.1	4.5	IE4
660	Y	50	15.00	-/-	15.60	2955	48.5	93.3	93.5	92.9	0.90	0.87	0.80	9.0	3.1	4.5	IE4
440	Δ	60	17.30	-/-	27.00	3555	46.5	93.0	93.0	92.1	0.90	0.88	0.81	8.8	3.0	4.3	IE4
440	Δ	60	15.00	-/-	24.00	3560	40.0	92.4	92.1	90.9	0.89	0.86	0.78	10.0	3.5	5.0	IE4

IM B3 / IM 1001		FS 160 M	98 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN		
-----------------	--	----------	-------	------	--	--------------	------------------------	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 25.3 s | 32.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	74.0 / 87.0 dB(A) ²⁾	79.0 / 92.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0680 kg m ²		Vibration severity grade	A
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1004-1DA33-3AA4			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-04-21 14:08	en	1/1