

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1104J - 100 L - (G) IM V1 / IM3011 - p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	1.90	-/-	4.40	1390	13.1	72.0			0.87			4.1	1.7	1.8	
400	YY	50	2.40	-/-	5.60	2800	8.2	70.0			0.88			4.2	1.8	1.8	
(G) IM V1 / IM3011		FS 100 L						IEC/EN 60034									
Environmental conditions : -20 °C - +40 °C / 1,000 m																	
Exception from EU 2019/1781 acc. to Article 2 (2) (n)																	

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) ³⁾	/ dB(A) ³⁾	Duty type	S1 = continuous operation
Moment of inertia	0.0059 kg m ²		Direction of rotation	bidirectional
Bearing DE NDE	6306 2ZC3	6306 2ZC3	Frame material	aluminum
Regreasing device	40000		Net weight of the motor	18 kg
Type of bearing	Preloaded bearing NDE		Coating (paint finish)	Standard paint finish C2
Condensate drainage holes	No		Color, paint shade	RAL7030
External earthing terminal	No		Motor protection	without
Vibration severity grade	A (standard)		Method of cooling	IC 411
Thermal class	F			

Terminal box

Terminal box position	Terminal box - at the top	Max. cross-sectional area	4 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal

M_K/M_N = locked rotor torque / torque nominal

M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010

2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet		document status		released	
	title	1LE1011-1AJ43-4GA4		document number			
© Siemens AG 2023				rev.	creation date	language	Page
				943	2023-03-28	en	1/1