Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS Motor type : 1AV1112P - 112 M - (G) IM V1 / IM3011 - p Offer no. Client order no. Item-No. Order no. Consignment no. Project Remarks Electrical data U Δ/Υ f Р Р ī М η 3) cosφ 3) I_A/I_N M_A/M_N M_K/M_N IE-CL n [V] [Hz] [kW] [hp] [A] [1/min] [Nm] I_I/I_N T_I/T_N T_B/T_N 4/4 3/4 2/4 4/4 3/4 2/4 400 50 -/-1455 83.4 0.85 400 50 2885 80.8 0.92 G) IM V1 / IM3011 FS 112 M IEC/EN 60034 27 kg Environmental conditions : ${}^{\circ}C - + {}^{\circ}C / m$ Mechanical data Sound level (SPL / SWL) at 50Hz|60Hz / dB(A) / dB(A) Insulation 155(F) to 130(B) Moment of inertia 0.0100 kg m² Duty type S1 = continuous operation Bearing DE | NDE 6306 2ZC3 6306 2ZC3 Direction of rotation bidirectional Lubricants Esso Unirex N3 Frame material aluminum Regreasing device Net weight of the motor 27 kg Type of bearing Preloaded bearing NDE Color, paint shade RAL7030 Condensate drainage holes without No Motor protection External earthing terminal No Method of cooling IC 411 Vibration severity grade A (standard) Terminal box Terminal box position Terminal box - at the top Max. cross-sectional area 4 mm^2 Cable diameter from ... to ... Material of terminal box Aluminium 11 mm - 21 mm Type of terminal box TB1 F00 Cable entry 2xM32x1,5 Contact screw thread M4 Cable gland 2 plugs Notes: 1) L10mh according to DIN ISO 281 10/2010 I_A/I_N = locked rotor current / current nominal 3) Value is valid only for DOL operation with motor design IC411 $M_A/M_N = locked rotor torque / torque nominal$ M_K/M_N = break down torque / nominal torque Technical data are subject to change! There may be discrepancies responsible dep. technical reference created by approved by between calculated and rating plate values. DI MC LVM **DT** Configurator document type document status customer datasheet released document number 1LE1011-1BP23-4GA4 creation date Page rev. language © Siemens AG 2021 2021-07-21 18:48 1/1