

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1162L

- 160 M - (F) IM B5 / IM3001 - p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50		-/-		730		77.5			0.57						
400	Y	50		-/-		1450		84.0			0.90						
(F) IM B5 / IM3001		FS 160 M		62 kg				IEC/EN 60034									

Environmental conditions : °C - + °C / m

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A)	/ dB(A)	Insulation	155(F) to 130(B)
Moment of inertia	0.0440 kg m ²		Duty type	S1 = continuous operation
Bearing DE NDE	6309 2ZC3		Direction of rotation	bidirectional
Lubricants	Esso Unirex N3		Frame material	aluminum
Regreasing device			Net weight of the motor	62 kg
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	No		Motor protection	without
External earthing terminal	No		Method of cooling	IC 411
Vibration severity grade	A (standard)			

Terminal box

Terminal box position	Terminal box - at the top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1011-1DL23-4FA4		document number			
© Siemens AG 2021				rev.	creation date	language	Page
				01	2021-04-22 15:08	en	1/1