

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1164L SIMOTICS GP - 160 L - (F) IM B5 / IM3001 - p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data -/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	5.60	-/-	16.80	725	73.8	80.2			0.60			4.0	1.9	2.7	
400	YY	50	11.00	-/-	21.00	1445	72.7	84.4			0.90			5.1	1.5	2.2	
(F) IM B5 / IM3001		FS 160 L						IEC/EN 60034									
Environmental conditions : -20 °C - +40 °C / 1000 m																	
Exception from EU 2019/1781 acc. to Article 2 (2) (n)																	

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) ³⁾	/ dB(A) ³⁾	Duty type	S1 = continuous operation
Moment of inertia	0.0560 kg m ²		Direction of rotation	bidirectional
Bearing DE NDE	6309 2ZC3	6309 2ZC3	Frame material	aluminum
Regreasing device	40000		Net weight of the motor	85 kg
Type of bearing	Locating bearing NDE		Coating (paint finish)	Standard paint finish C2
Condensate drainage holes	No		Color, paint shade	RAL7030
External earthing terminal	No		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Vibration severity grade	A (standard)		Method of cooling	IC 411
Thermal class	F			

Terminal box position	Terminal box - at the top	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

I_A/I_N = locked rotor current / current nominal 1) L_{10min} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
M_B/M_N = break down torque / nominal torque

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	Document type Technical data sheet			Document status Released			
	Document title 1LE1011-1DL43-4FB4-Z			Document number TDS-240614-120358			
Restricted © Innomotics 2024	D47			Revision AA	Creation date 2024-06-14	Language en	Page 1/2

SIMOTICS GP - 160 L - (F) IM B5 / IM3001 - p

Special design

D47	TR CU product safety certificate EAC for the Eurasian Customs Union
-----	---

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	Document type Technical data sheet			Document status Released			
	Document title 1LE1011-1DL43-4FB4-Z			Document number TDS-240614-120358			
Restricted © Innomotics 2024	D47			Revision AA	Creation date 2024-06-14	Language en	Page 2/2