

SIMOTICS GP - 132 M - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	7.50	-/-	15.80	1465	49.0	90.4	90.7	90.4	0.80	0.74	0.63	8.5	3.0	3.8	IE3
440	Δ	60	8.60	-/-	15.60	1765	46.5	89.5	90.0	89.4	0.81	0.76	0.65	8.8	3.0	3.8	IE2
440	Δ	60	7.50	10.00	13.50	1770	40.5	91.7	91.6	90.6	0.79	0.73	0.61	9.8	3.4	4.3	MG1
IM V1 / IM 3011			FS 132 M		CC032A		IP55	UKCA		IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12			kVA Code: N		
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 14.8 s 20.1 s								

Sound level (SPL / SWL) at 50Hz 60Hz	72 / 80 dB(A) ^{2) 3)}	68 / 76 dB(A) ^{2) 3)}	External earthing terminal	Without
Moment of inertia	0.0334 kg m²		Vibration severity grade	A
Bearing DE NDE	6208 Z C3	6208 Z C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g 8000 h		Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	61 kg
Regreasing device	With		Coating (paint finish)	Special paint finish C3
Grease nipple	M8x1 DIN 71412		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	6 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_L/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE1023-1CB23-3GB4-Z B02+L23+Q02+S02			document number			
© Siemens AG 2023				rev. 943	creation date 2023-04-27	language en	Page 1/2

SIMOTICS GP - 132 M - IM V1 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Q02	Anti-condensation heating for 230 V (2 terminals)
L23	Regreasing system	S02	Special paint finish C3

Additional information:

Space heaters

Technical data:	1-phase, 230 V 50W
-----------------	--------------------

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1023-1CB23-3GB4-Z						
	B02+L23+Q02+S02			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-04-27	en	2/2