

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3164A

SIMOTICS GP - 160 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	18.50	-/-	32.00	2955	60.0	92.4	92.8	92.3	0.90	0.87	0.80	8.3	2.8	3.9	IE3
690	Y	50	18.50	-/-	18.60	2955	60.0	92.4	92.8	92.3	0.90	0.87	0.80	8.3	2.8	3.9	IE3
460	Δ	60	21.30	-/-	32.00	3550	57.0	91.7	91.8	91.1	0.91	0.89	0.82	8.2	2.7	3.8	IE3
460	Δ	60	18.50	-/-	28.00	3560	49.5	91.7	91.5	90.3	0.90	0.87	0.79	9.4	3.1	4.4	IE3
IM B3 / IM 1001		FS 160 L		94 kg		IP56		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						KS C IEC60034-2-1	

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 4.16 s | 6.22 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70.0 / 82.0 dB(A) ²⁾	77.0 / 89.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0680 kg m ²		Vibration severity grade	A
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.				
DI MC LVM		DT Configurator						
	document type	datasheet			document status		customer	
					released			
		title	1LE1043-1DA43-4AB4-Z			document number		
	B02+D33+H22				rev.	creation date	language	Page
© Siemens AG 2021					01	2021-04-22 07:44	en	1/2

SIMOTICS GP - 160 L - IM B3 - 2p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	H22	IP 56 degree of protection
D33	For Korea, certified according to KS C IEC 60034-2-1		

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1043-1DA43-4AB4-Z						
	B02+D33+H22			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-22 07:44	en	2/2