

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3162C

SIMOTICS GP - 160 M - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	7.50	-/-	15.00	985	73.0	89.1	89.5	88.6	0.81	0.76	0.65	7.9	2.3	3.2	IE3
690	Y	50	7.50	-/-	8.70	985	73.0	89.1	89.5	88.6	0.81	0.76	0.65	7.9	2.3	3.2	IE3
460	Δ	60	8.60	-/-	14.50	1185	69.0	91.0	91.3	90.2	0.82	0.77	0.67	8.3	2.3	3.3	IE3
460	Δ	60	7.50	-/-	12.90	1185	60.0	91.0	90.8	89.4	0.80	0.74	0.63	9.3	2.7	3.7	IE3

IM B3 / IM 1001		FS 160 M	95 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN		KS C IEC60034-2-1
-----------------	--	----------	-------	------	--	--------------	------------------------	--	-------------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19.6 s | 25 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 79 dB(A) ²⁾	70 / 82 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.1320 kg m ²		Vibration severity grade	A
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	right	Max. cross-sectional area	16 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J00	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1043-1DC23-4AF5-Z			
	B02+D33+G11			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-08-20 11:09	en	1/2

SIMOTICS GP - 160 M - IM B3 - 6p

B02	Acceptance test certificate 3.1 acc. to EN 10204	G11	Rotary pulse encoder Sendix 5020 (HTL)
D33	For Korea, certified according to KS C IEC 60034-2-1		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1043-1DC23-4AF5-Z			document number			
© Siemens AG 2021	B02+D33+G11			rev. 01	creation date 2021-08-20 11:09	language en	Page 2/2