

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2083D

SIMOTICS SD - 80 M - IM B14 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _i /I _N	T _i /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.25	-/-	2.25	705	3.4	50.6	48.1	41.9	0.55	0.46	0.37	2.5	2.0	2.5	IE2
400	Y	50	0.25	-/-	1.30	705	3.4	50.6	48.1	41.9	0.55	0.46	0.37	2.5	2.0	2.5	IE2
460	Y	60	0.28	-/-	1.27	855	3.2	52.0	49.7	44.2	0.55	0.46	0.37	2.7	1.9	2.6	IE2
460	Y	60	0.25	-/-	1.21	860	2.8	52.0	49.0	43.0	0.51	0.43	0.35	2.9	2.2	3.0	IE2
IM B14 / IM 3601			FS 80 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1.000 m									Locked rotor time (hot / cold) : 45.8 s 62.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	51 / 62 dB(A) ^{2) 3)}	55 / 66 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0025 kg m ²		Thermal class	F
Bearing DE NDE	6204 2Z C3	6204 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	18 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 D01	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents			
DI MC LVM		DT Configurator							
	document type					document status			
	datasheet					released			
	title					document number			
	1LE1501-0DD32-2KA4-Z								
	D47					rev.	creation date	language	Page
© Siemens AG 2022						01	2022-08-12	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2083D

SIMOTICS SD - 80 M - IM B14 - 8p

Special design

D47 TR CU product safety certificate EAC for the Eurasian Customs Union

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1501-0DD32-2KA4-Z D47				document number
© Siemens AG 2022				rev. 01	creation date 2022-08-12
				language en	Page 2/2

