

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2130B

SIMOTICS SD - 132 S - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
460	Δ	60	6.30	-/-	10.90	1765	34.0	89.5	90.0	89.1	0.81	0.76	0.66	7.3	2.3	2.9	IE2
IM B5 / IM 3001			FS 132 S		61 kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 14.3 s 22.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64.0 / 76.0 dB(A) ²⁾	68.0 / 80.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0220 kg m ²		Vibration severity grade	A
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	3 Bi-metallic sensors (opener) for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1501-1CB09-0FZ4-Z	document number						
	© Siemens AG 2021	F01+F11+F50+H07+M1F+Q02+Q3A			rev. 01	creation date 2021-04-23 08:30	language en	Page 1/2

SIMOTICS SD - 132 S - IM B5 - 4p

F01	Mounting a brake	M1F	460 VD for 60 Hz, 60-Hz power
F11	Brake supply voltage, 230 V AC, 50/60 Hz	Q02	Anti-condensation heating for 230 V (2 terminals)
F50	Mechanical manual brake release with lever (cannot be locked)	Q3A	1/3 Bi-metallic sensors (opener) for tripping (2 terminals)
H07	Stainless steel screws and bolts (outside the motor)		

Space heaters

Technical data: 1-phase, 230 V 50W

Brake:

Description:	BFK458-16	Current:	.27 A
Voltage:	AC 230 V	Moment of inertia:	.0015 Nm

Notes:

responsible dep.		technical reference		created by		approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM				DT Configurator							
		document type				document status			customer		
		datasheet				released					
		title				document number					
		1LE1501-1CB09-0FZ4-Z									
© Siemens AG 2021		F01+F11+F50+H07+M1F+Q02+Q3A				rev.		creation date		language	Page
						01		2021-04-23 08:30		en	2/2