

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2163A

SIMOTICS SD - 160 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
400	Δ	50	14.39	-/-	26.50	2955	46.5	90.4	90.6	89.8	0.87	0.82	0.71	7.9	2.5	3.5	IE2
690	Y	50	14.39	-/-	15.30	2955	46.5	90.4	90.6	89.8	0.87	0.82	0.71	7.9	2.5	3.5	IE2
460	Δ	60	16.60	-/-	26.00	3555	44.6	91.0	91.2	90.0	0.89	0.86	0.80	7.9	2.5	3.5	IE2
460	Δ	60	15.00	-/-	24.00	3565	40.0	90.2	90.0	88.6	0.87	0.84	0.76	8.4	2.8	3.9	IE2
IM B3 / IM 1001		FS 160 M		104 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +45 °C / 1,000 m

Locked rotor time (hot / cold) : 12.1 s | 23 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70.0 / 82.0 dB(A) ²⁾	77.0 / 89.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0530 kg m ²		Vibration severity grade	A
Bearing DE NDE	6209 Z C3	6209 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish for offshore applications C5
Regreasing device	Yes		Color, paint shade	RAL7030
Grease nipple	M8x1 DIN 71412		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1501-1DA33-4AA4-Z B02+F74+L20+L23+M11+N05+Q02+R11+R62+S04			
© Siemens AG 2021		rev.	creation date	language
		01	2021-04-22 21:05	en
				Page
				1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2163A

SIMOTICS SD - 160 M - IM B3 - 2p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	N05	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 45°C, power reduced
F74	Sheet steel fan cowl	Q02	Anti-condensation heating for 230 V (2 terminals)
L20	Locating bearing, DE	R11	Terminal box rotated through 90°, cable entry from NDE
L23	Regreasing system	R62	Cast iron auxiliary terminal box (small)
M11	Stainless steel rating plate	S04	Special paint finish for offshore applications C5

Additional information:

Space heaters

Technical data: 1-phase, 230 V 50W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1501-1DA33-4AA4-Z	document number					
© Siemens AG 2021	B02+F74+L20+L23+M11+N05+Q02+R11+R62+S04		rev. 01	creation date 2021-04-22 21:05	language en	Page 2/2	