

SIMOTICS SD - 160 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

--

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	15.00	-/-	27.00	2955	48.5	90.3	90.7	90.0	0.88	0.83	0.73	7.6	2.4	3.4	IE2
690	Y	50	15.00	-/-	15.80	2955	48.5	90.3	90.7	90.0	0.88	0.83	0.73	7.6	2.4	3.4	IE2
460	Δ	60	17.30	-/-	27.00	3555	46.5	91.0	91.3	90.3	0.89	0.87	0.81	7.6	2.4	3.4	IE2
460	Δ	60	15.00	-/-	24.00	3565	40.0	90.2	90.0	88.6	0.87	0.84	0.76	8.4	2.8	3.9	IE2
IM B3 / IM 1001			FS 160 M		104 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Locked rotor time (hot / cold) : 12.1 s | 23 s

Sound level (SPL / SWL) at 50Hz 60Hz	70.0 / 82.0 dB(A) ²⁾	77.0 / 89.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0530 kg m²		Vibration severity grade	A
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	16.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

I_{Lr}/I_{N_r} = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_{Lr}/M_{N_r} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_{N_r} = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1501-1DA33-4AA4-Z			document number				
© Siemens AG 2021	B02			rev. 01	creation date 2021-04-23 13:31	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2163A

SIMOTICS SD - 160 M - IM B3 - 2p

Special design

B02 Acceptance test certificate 3.1 acc. to EN 10204

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1501-1DA33-4AA4-Z				document number			
© Siemens AG 2021	B02				rev. 01	creation date 2021-04-23 13:31	language en	Page 2/2