

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2162B

SIMOTICS SD - 160 M - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
380	Δ	50	10.12	-/-	20.50	1470	65.8	90.2	91.0	90.8	0.84	0.80	0.70	7.3	2.3	3.0	IE2
660	Y	50	10.12	-/-	11.70	1470	65.8	90.2	91.0	90.8	0.84	0.80	0.70	7.3	2.3	3.0	IE2
440	Δ	60	11.59	-/-	19.80	1770	62.5	91.2	91.6	90.7	0.84	0.81	0.72	7.6	2.4	3.0	IE2
440	Δ	60	11.00	-/-	18.90	1775	59.0	91.0	91.2	90.1	0.84	0.80	0.71	7.7	2.5	3.2	IE2

IM V1 / IM 3011		FS 160 M	96 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN										
-----------------	--	----------	-------	------	--	--------------	------------------------	--	--	--	--	--	--	--	--	--	--

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 17.9 s | 28.8 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 77.0 dB(A) ₂₎	69.0 / 81.0 dB(A) ₂₎	External earthing terminal	Yes
Moment of inertia	0.0550 kg m ²		Vibration severity grade	A
Bearing DE NDE	6209 Z C3	6209 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Regreasing device	Yes		Color, paint shade	RAL7030
Grease nipple	M8x1 DIN 71412		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

¹⁾ L10mh according to DIN ISO 281 10/2010
²⁾ at rated power / at full load

³⁾ Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1501-1DB23-3GA4-Z			
	B02+H04+L23+N06+N30+S03			
© Siemens AG 2021		rev.	creation date	language Page
		01	2021-07-09 10:48	en 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2162B

SIMOTICS SD - 160 M - IM V1 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	N06	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 50°C, power reduced
H04	External grounding at housing	N30	Increased air humidity/temperature with 30 to 60 g water per m3 air
L23	Regreasing system	S03	Special paint finish in sea air resistant C4

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1501-1DB23-3GA4-Z							
© Siemens AG 2021	B02+H04+L23+N06+N30+S03	rev. 01	creation date 2021-07-09 10:48		language en	Page 2/2		