

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2164C

SIMOTICS SD - 160 L - IM V5 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	11.00	-/-	23.50	975	108.0	88.7	89.7	89.3	0.76	0.71	0.60	4.8	1.9	2.2	IE2
690	Y	50	11.00	-/-	13.70	975	108.0	88.7	89.7	89.3	0.76	0.71	0.60	4.8	1.9	2.2	IE2
460	Δ	60	12.60	-/-	23.00	1175	102.0	90.2	91.1	90.7	0.76	0.72	0.62	4.9	1.9	2.2	IE2
460	Δ	60	11.00	-/-	20.50	1180	89.0	90.2	90.5	89.5	0.74	0.69	0.58	5.5	2.2	2.5	IE2
IM V5 / IM 1011		FS 160 L		IP55				IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 33.6 s 54.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 79 dB(A) ²⁾	70 / 82 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0980 kg m ²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	122 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	left	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet			document status	released	
	title	1LE1501-1DC43-4CA6-Z			document number		
© Siemens AG 2022	D22	rev.	creation date		language	Page	
		01	2022-02-02		en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2164C

SIMOTICS SD - 160 L - IM V5 - 6p

Special design

D22 Motor without CE character for export outside the EEA (see EU regulation 2019/1781)

Notes:

responsible dep.

DI MC LVM

technical reference

created by

DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type

datasheet

title

1LE1501-1DC43-4CA6-Z

D22

document status

released

document number

rev.

01

creation date

2022-02-02

language

en

Page

2/2

© Siemens AG 2022

