

SIMOTICS SD - 180 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
400	Δ	50	22.00	-/-	40.00	2940	71.0	91.3	91.8	91.3	0.87	0.83	0.74	7.4	2.7	3.6	IE2
690	Y	50	22.00	-/-	23.00	2940	71.0	91.3	91.8	91.3	0.87	0.83	0.74	7.4	2.7	3.6	IE2
460	Δ	60	24.50	-/-	39.00	3540	66.0	91.0	91.2	90.3	0.87	0.83	0.75	7.7	2.8	3.8	IE2
460	Δ	60	22.00	-/-	35.50	3550	59.0	91.0	91.2	90.3	0.86	0.82	0.74	8.4	3.0	4.1	IE2

IM B3 / IM 1001	FS 180 M	145 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	----------	--------	------	--------------	------------------------

Locked rotor time (hot / cold) : 10.4 s | 19.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	77.0 / 84.0 dB(A) ²⁾	80.0 / 87.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.0690 kg m ²		Vibration severity grade	A
Bearing DE NDE	6210 Z C3	6210 Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	1 gland, 1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1501-1EA23-4AA4-Z				
	F74+F76+H01+N03+R11+R15	rev.	creation date	language	Page
© Siemens AG 2021		01	2021-04-21 12:03	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2182A

SIMOTICS SD - 180 M - IM B3 - 2p

Special design

F74	Sheet steel fan cowl	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
F76	Metal external fan	R11	Terminal box rotated through 90°, cable entry from NDE
H01	Bolted on mounting feet (instead of cast)	R15	One metal cable gland

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1501-1EA23-4AA4-Z			document number				
© Siemens AG 2021	F74+F76+H01+N03+R11+R15			rev. 01	creation date 2021-04-21 12:03	language en	Page 2/2	