

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2182B

SIMOTICS SD - 180 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	18.50	-/-	35.00	1465	121.0	91.2	92.0	91.9	0.84	0.79	0.69	7.2	2.5	3.4	IE2
690	Y	50	18.50	-/-	20.00	1465	121.0	91.2	92.0	91.9	0.84	0.79	0.69	7.2	2.5	3.4	IE2
460	Δ	60	21.30	-/-	34.00	1765	115.0	92.4	93.0	92.7	0.85	0.81	0.72	6.8	2.5	3.4	IE2
460	Δ	60	18.50	-/-	30.50	1770	100.0	92.4	92.6	91.9	0.83	0.78	0.67	7.7	2.8	3.9	IE2
IM B3 / IM 1001		FS 180 M		160 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 11.8 s | 21.4 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	61.0 / 74.0 dB(A) ²⁾	64.0 / 77.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.1200 kg m ²		Vibration severity grade	A
Bearing DE NDE	6210 Z C3	6210 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	3 Bi-metallic sensors (opener) for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status		customer	
				released			
	title	1LE1501-1EB23-4AZ4-Z		document number			
© Siemens AG 2021	D22+D47+Q3A			rev.	creation date	language	Page
	01			2021-04-23 15:21	en	1/2	

SIMOTICS SD - 180 M - IM B3 - 4p

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	Q3A	1/3 Bi-metallic sensors (opener) for tripping (2 terminals)
D47	TR CU product safety certificate EAC for the Eurasian Customs Union		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1501-1EB23-4AZ4-Z			document number			
© Siemens AG 2021	D22+D47+Q3A			rev. 01	creation date 2021-04-23 15:21	language en	Page 2/2