

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2186B

SIMOTICS SD - 180 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	58.00	1465	196.0	92.3	92.8	92.6	0.81	0.76	0.66	7.3	2.5	3.3	IE2
690	Y	50	30.00	-/-	33.50	1465	196.0	92.3	92.8	92.6	0.81	0.76	0.66	7.3	2.5	3.3	IE2
460	Δ	60	34.50	-/-	57.00	1765	187.0	93.0	93.5	93.2	0.82	0.78	0.69	7.7	2.3	3.3	IE2
460	Δ	60	30.00	-/-	51.00	1770	162.0	93.0	93.1	92.3	0.80	0.75	0.65	8.7	2.6	3.9	IE2
IM B3 / IM 1001		FS 180 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 14.8 s 28.5 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 77 dB(A) ²⁾	71 / 78 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.1590 kg m ²		Thermal class	F
Bearing DE NDE	6210 Z C3	6210 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz Lubricants	40000 h	32000 h	Frame material	cast iron
Regreasing device	Unirex N3		Net weight of the motor (IM B3)	185 kg
Grease nipple	No		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	Yes (standard)		Motor protection	(A) without (Standard)
External earthing terminal	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1501-1EB63-4AA4-Z						
	D22+D47			rev.	creation date	language	Page
© Siemens AG 2022				01	2022-01-28	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2186B

SIMOTICS SD - 180 L - IM B3 - 4p

Special design

D22	Motor without CE character for export outside the EEA (see EU regulation 2019/1781)	D47	TR CU product safety certificate EAC for the Eurasian Customs Union
-----	---	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE1501-1EB63-4AA4-Z			document number			
D22+D47				rev. 01	creation date 2022-01-28	language en	Page 2/2
© Siemens AG 2022							