

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2184D

SIMOTICS SD - 180 L - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	11.00	-/-	27.50	720	146.0	86.9	88.0	87.6	0.70	0.63	0.51	4.9	2.3	2.6	IE2
660	Y	50	11.00	-/-	15.80	720	146.0	86.9	88.0	87.6	0.70	0.63	0.51	4.9	2.3	2.6	IE2
440	Δ	60	13.20	-/-	27.00	865	146.0	88.5	90.1	90.3	0.73	0.67	0.56	4.9	2.2	2.4	IE1
440	Δ	60	11.00	-/-	23.50	875	120.0	88.5	89.1	88.3	0.69	0.62	0.49	5.6	2.6	2.9	IE2
IM B3 / IM 1001		FS 180 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 39.3 s 67.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 79 dB(A) ^{2) 3)}	75 / 79 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1950 kg m ²		Thermal class	F
Bearing DE NDE	6210 2Z C3	6210 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	155 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled
External earthing terminal	Yes (standard)			

Terminal box

Terminal box position	right	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1501-1ED43-3AA5-Z				
	F70				
© Siemens AG 2022		rev.	creation date	language	Page
		01	2022-07-12	en	1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2184D

SIMOTICS SD - 180 L - IM B3 - 8p

Special design

F70 Mounting of separately driven fan

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE1501-1ED43-3AA5-Z			document number			
© Siemens AG 2022	F70			rev. 01	creation date 2022-07-12	language en	Page 2/2