

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2205B

SIMOTICS SD - 200 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
500	Δ	50	30.00	-/-	44.50	1470	195.0	92.3	92.9	92.6	0.84	0.80	0.70	6.7	2.5	3.3	IE2
575	Δ	60	34.50	-/-	44.00	1770	186.0	93.0	93.5	93.1	0.85	0.81	0.73	7.2	2.7	3.2	IE2
575	Δ	60	30.00	-/-	38.50	1778	161.0	93.0	93.1	92.3	0.84	0.79	0.69	8.2	3.2	3.7	IE2
IM B3 / IM 1001		FS 200 L		230 kg		IP55	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 13.4 s 24.5 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70.0 / 77.0 dB(A) ²⁾	72.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.2000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6212 C3	6212 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	25.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M6	Cable gland	2 plugs

Notes:		
I _L /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _L /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status		customer	
				released			
	title	1LE1501-2AB54-0AA4-Z		document number			
© Siemens AG 2021	L23			rev.	creation date	language	Page
						01	2021-04-23 13:33

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2205B

SIMOTICS SD - 200 L - IM B3 - 4p

Special design

L23 Regreasing system

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1501-2AB54-0AA4-Z				document number			
© Siemens AG 2021	L23				rev. 01	creation date 2021-04-23 13:33	language en	Page 2/2