

SIMOTICS SD - 225 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	45.00	-/-	79.00	2965	145.0	92.9	93.1	92.5	0.88	0.85	0.76	7.8	2.7	3.7	IE2
690	Y	50	45.00	-/-	46.00	2965	145.0	92.9	93.1	92.5	0.88	0.85	0.76	7.8	2.7	3.7	IE2
460	Δ	60	51.00	-/-	78.00	3565	137.0	93.0	93.0	92.0	0.88	0.85	0.78	7.6	2.7	3.7	IE2
460	Δ	60	45.00	-/-	69.00	3570	120.0	93.0	92.7	91.3	0.88	0.84	0.76	8.7	3.1	3.8	IE2
IM B3 / IM 1001			FS 225 M		295 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 20.2 s | 33.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	76.0 / 89.0 dB(A) ²⁾	77.0 / 90.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.2300 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad,min} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1501-2BA23-4AB4-Z			document number				
© Siemens AG 2021	H01+L51+M11			rev. 01	creation date 2021-04-20 23:18	language en	Page 1/2	

SIMOTICS SD - 225 M - IM B3 - 2p

H01	Bolted on mounting feet (instead of cast)	M11	Stainless steel rating plate
L51	Bearing insulation NDE		

--

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1501-2BA23-4AB4-Z			document number			
© Siemens AG 2021	H01+L51+M11			rev. 01	creation date 2021-04-20 23:18	language en	Page 2/2