

SIMOTICS SD - 225 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_A/I_N	T_A/T_N	T_B/T_N	
500	Δ	50	45.00	-/-	64.00	2965	145.0	92.9	93.1	92.5	0.88	0.85	0.76	7.8	2.7	3.7	IE2
575	Δ	60	51.00	-/-	63.00	3565	137.0	93.0	93.0	92.0	0.88	0.85	0.78	7.6	2.7	3.7	IE2
575	Δ	60	45.00	-/-	55.00	3570	120.0	93.0	92.7	91.3	0.88	0.84	0.76	8.7	3.1	3.8	IE2
IM B3 / IM 1001			FS 225 M		295 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 20.2 s | 33.6 s

Sound level (SPL / SWL) at 50Hz 60Hz	72.4 / 86.0 dB(A) ²⁾	76.4 / 90.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.2300 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	35.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

I_L/I_N = locked rotor current / current nominal	1) L10mth according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_L/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1501-2BA24-0AB4-Z F70+G05+L51+Y81			document number			
© Siemens AG 2021				rev. 01	creation date 2021-04-23 15:49	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2222A

SIMOTICS SD - 225 M - IM B3 - 2p

Special design

F70	Mounting of separately driven fan	L51	Bearing insulation NDE
G05	Mounting a rotary pulse encoder HOG 9 D 1024 l	Y81	External fan with non-standard voltage and/or frequency:

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1501-2BA24-0AB4-Z F70+G05+L51+Y81							document number
© Siemens AG 2021		rev. 01	creation date 2021-04-23 15:49		language en	Page 2/2		