

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2220B

SIMOTICS SD - 225 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	37.00	-/-	65.00	1470	240.0	92.7	93.5	93.5	0.88	0.85	0.78	6.6	2.3	2.9	IE2
690	Y	50	37.00	-/-	38.00	1470	240.0	92.7	93.5	93.5	0.88	0.85	0.78	6.6	2.3	2.9	IE2
460	Δ	60	42.50	-/-	65.00	1770	230.0	93.6	94.2	94.0	0.88	0.86	0.79	6.6	2.3	2.9	IE2
460	Δ	60	37.00	-/-	57.00	1778	199.0	93.0	93.2	92.5	0.87	0.84	0.76	7.2	2.7	3.3	IE2
IM B3 / IM 1001		FS 225 S		280 kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 16.2 s 29.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66.0 / 79.0 dB(A) ²⁾	69.0 / 82.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.4200 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	2 glands, 2 plugs

Notes:		
I _L /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _L /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released	customer	
	title 1LE1501-2BB03-4AB4-Z				document number		
	© Siemens AG 2021	R18	rev. 01	creation date 2021-04-22 21:29	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2220B

SIMOTICS SD - 225 S - IM B3 - 4p

Special design

R18

Cable gland metal, max. number

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1501-2BB03-4AB4-Z							
© Siemens AG 2021	R18	rev. 01	creation date 2021-04-22 21:29		language en	Page 2/2		