

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2222B

SIMOTICS SD - 225 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	45.00	-/-	80.00	1475	290.0	93.1	93.8	93.7	0.87	0.84	0.76	6.9	2.5	3.1	IE2
690	Y	50	45.00	-/-	46.50	1475	290.0	93.1	93.8	93.7	0.87	0.84	0.76	6.9	2.5	3.1	IE2
460	Δ	60	52.00	-/-	80.00	1775	280.0	94.1	94.7	94.4	0.87	0.85	0.78	6.8	2.5	3.1	IE2
460	Δ	60	45.00	-/-	70.00	1778	240.0	93.6	93.8	93.1	0.86	0.83	0.74	7.6	3.0	3.5	IE2
IM B3 / IM 1001		FS 225 M		305 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 14.4 s | 26.3 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66.0 / 79.0 dB(A) ²⁾	69.0 / 83.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.4600 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(J) 6 resistance thermometers PT100 (12 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1501-2BB23-4AJ4-Z Q72+Q82+Y53			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-04-22 15:44	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2222B

SIMOTICS SD - 225 M - IM B3 - 4p

Special design

Q72	2 Pt100 resistance thermometers in basic configuration for bearings (4 terminals)	Y53	Paint finish in other standard RAL colours
Q82	Extension of the liability for defects by 24 months to a total of 36 months (3 years) from delivery		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1501-2BB23-4AJ4-Z	document number					
© Siemens AG 2021	Q72+Q82+Y53	rev. 01	creation date 2021-04-22 15:44	language en	Page 2/2		