

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2226B

SIMOTICS SD - 225 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	55.00	-/-	101.00	1475	355.0	93.5	94.2	94.1	0.84	0.80	0.71	5.8	2.5	2.7	IE2
690	Y	50	55.00	-/-	59.00	1475	355.0	93.5	94.2	94.1	0.84	0.80	0.71	5.8	2.5	2.7	IE2
460	Δ	60	63.00	-/-	99.00	1775	340.0	94.1	94.7	94.6	0.85	0.82	0.74	6.2	2.5	2.6	IE2
460	Δ	60	55.00	-/-	87.00	1780	295.0	94.1	94.4	94.0	0.84	0.80	0.70	7.1	2.8	3.0	IE2
IM B5 / IM 3001		FS 225 M		320 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - + °C / 1,000 m

Locked rotor time (hot / cold) : 27.7 s | 46.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	72.4 / 86.0 dB(A) ²⁾	76.4 / 90.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.4700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(C) 6 PTC thermistors - for alarm and tripping (4 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	2 glands, 2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number	rev.	creation date
	1LE1501-2BB63-4FC4-Z		01	2021-04-21 09:43
	F70+L51+N03+N30+Q82+R18+R62+Y82			
© Siemens AG 2021			language	Page
			en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2226B

SIMOTICS SD - 225 M - IM B5 - 4p

Special design

F70	Mounting of separately driven fan	Q82	Extension of the liability for defects by 24 months to a total of 36 months (3 years) from delivery
L51	Bearing insulation NDE	R18	Cable gland metal, max. number
N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature	R62	Cast iron auxiliary terminal box (small)
N30	Increased air humidity/temperature with 30 to 60 g water per m3 air	Y82	Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1501-2BB63-4FC4-Z				document number			
© Siemens AG 2021	F70+L51+N03+N30+Q82+R18+R62+Y82			rev. 01	creation date 2021-04-21 09:43	language en	Page 2/2	