

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2252B

SIMOTICS SD - 250 M - IM B3 - 4p

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

Remarks

Electrical data

Safe Area

| U               | Δ / Y | f        | P     | P      | I      | n       | M     | η <sup>3)</sup> |      |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------|-------|----------|-------|--------|--------|---------|-------|-----------------|------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]             |       | [Hz]     | [kW]  | [hp]   | [A]    | [1/min] | [Nm]  | 4/4             | 3/4  | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| 400             | Δ     | 50       | 55.00 | -/-    | 100.00 | 1480    | 355.0 | 93.5            | 93.9 | 93.5                   | 0.85               | 0.81 | 0.72 | 6.8                            | 2.7                            | 3.0                            | IE2   |
| 690             | Y     | 50       | 55.00 | -/-    | 58.00  | 1480    | 355.0 | 93.5            | 93.9 | 93.5                   | 0.85               | 0.81 | 0.72 | 6.8                            | 2.7                            | 3.0                            | IE2   |
| 460             | Δ     | 60       | 63.00 | -/-    | 99.00  | 1780    | 340.0 | 94.1            | 94.4 | 94.0                   | 0.85               | 0.82 | 0.74 | 6.6                            | 2.8                            | 2.9                            | IE2   |
| 460             | Δ     | 60       | 55.00 | -/-    | 87.00  | 1785    | 295.0 | 94.1            | 94.1 | 93.3                   | 0.84               | 0.80 | 0.71 | 7.3                            | 3.1                            | 3.3                            | IE2   |
| IM B3 / IM 1001 |       | FS 250 M |       | 385 kg |        | IP55    |       | IEC/EN 60034    |      | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19.9 s | 34.1 s

Mechanical data

|                                                                                     |                                 |                                 |                            |                                                    |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 66.0 / 79.0 dB(A) <sup>2)</sup> | 69.0 / 83.0 dB(A) <sup>2)</sup> | External earthing terminal | Yes (standard)                                     |
| Moment of inertia                                                                   | 0.7500 kg m <sup>2</sup>        |                                 | Vibration severity grade   | A                                                  |
| Bearing DE   NDE                                                                    | 6215 Z C3                       | 6215 Z C3                       | Insulation                 | 155(F) to 130(B)                                   |
| bearing lifetime                                                                    |                                 |                                 | Duty type                  | S1                                                 |
| L <sub>10mh</sub> F <sub>Rad min</sub> 50 60Hz <sup>1)</sup> for coupling operation | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                                      |
| Lubricants                                                                          | Unirex N3                       |                                 | Frame material             | cast iron                                          |
| Regreasing device                                                                   | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                           |
| Grease nipple                                                                       | -/-                             |                                 | Color, paint shade         | RAL7030                                            |
| Type of bearing                                                                     | Locating bearing NDE            |                                 | Motor protection           | (B) 3 PTC thermistors - for tripping (2 terminals) |
| Condensate drainage holes                                                           | Yes (standard)                  |                                 | Method of cooling          | IC411 - self ventilated, surface cooled            |

Terminal box

|                          |           |                                |                       |
|--------------------------|-----------|--------------------------------|-----------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 120.0 mm <sup>2</sup> |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 34.0 mm - 42.0 mm     |
| Type of terminal box     | TB1 N01   | Cable entry                    | 2xM63x1,5-2xM20x1,5   |
| Contact screw thread     | M10       | Cable gland                    | 4 plugs               |

Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
M<sub>K</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                   |                     |                    |             |                                                                                                              |                  |          |      |
|-------------------|---------------------|--------------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.  | technical reference | created by         | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM         |                     | DT Configurator    |             |                                                                                                              |                  |          |      |
|                   | document type       | datasheet          |             | document status                                                                                              |                  | customer |      |
|                   | title               | 1LE1501-2CB23-4AB4 |             | released                                                                                                     |                  |          |      |
| © Siemens AG 2021 |                     |                    |             | document number                                                                                              |                  |          |      |
|                   |                     |                    |             | rev.                                                                                                         | creation date    | language | Page |
|                   |                     |                    |             | 01                                                                                                           | 2021-04-23 11:37 | en       | 1/1  |