

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2252C

SIMOTICS SD - 250 M - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
								4/4	3/4	2/4	4/4	3/4	2/4	I _i /I _N	T _i /T _N	T _B /T _N		
IM B3 / IM 1001			FS 250 M		370 kg		IP55				IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 21.4 s 33.7 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	62.0 / 77.0 dB(A) ²⁾	66.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.8600 kg m ²		Vibration severity grade	A
Bearing DE NDE	6215 Z C3	6215 Z C3	Insulation	180(H) to 180(H)
bearing lifetime			Duty type	S1
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_K/M_N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released		customer			
	title 1LE1501-2CC29-0AB4-Z G16+M1Y+N10	document number					
© Siemens AG 2021		rev. 01	creation date 2021-04-22 16:29	language en	Page 1/2		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2252C

SIMOTICS SD - 250 M - IM B3 - 6p

Special design

G16	Mounting of HOG 10 DN 1024 I rotary pulse encoder, terminal box dust protection	N10	Temperature class 180 (H)
M1Y	Non-standard winding:		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1501-2CC29-0AB4-Z			document number				
© Siemens AG 2021	G16+M1Y+N10			rev. 01	creation date 2021-04-22 16:29	language en	Page 2/2	