

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1CV2280B

INNOMOTICS SD - 280 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks	Safe Area
Electrical data	-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	75.00	-/-	139.00	1485	480.0	94.0	94.2	93.8	0.87	0.85	0.78	6.8	2.5	3.0	IE2
660	Y	50	75.00	-/-	80.00	1485	480.0	94.0	94.2	93.8	0.87	0.85	0.78	6.8	2.5	3.0	IE2
440	Δ	60	86.00	-/-	136.00	1785	460.0	94.5	94.6	94.0	0.88	0.86	0.80	6.7	2.5	2.8	IE2
440	Δ	60	75.00	-/-	120.00	1788	400.0	94.5	94.3	93.2	0.87	0.84	0.77	7.6	2.7	3.2	IE2
IM B3 / IM 1001		FS 280 S				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 24.1 s 47.1 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	71 / 85 dB(A) ^{2) 3)}	79 / 92 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	1.3000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	550 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE1501-2DB03-3AB4-Z			Document number TDS-240923-122308			
Restricted © Innomotics 2024	D22			Revision AA	Creation date 2024-09-23	Language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1CV2280B

INNOMOTICS SD - 280 S - IM B3 - 4p

Special design

D22

Motor without CE character for export outside the EEA (see EU regulation 2019/1781)

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
INNOMOTICS	Document type Technical data sheet			Document status Released			
	Document title 1LE1501-2DB03-3AB4-Z			Document number TDS-240923-122308			
Restricted © Innomotics 2024	D22			Revision AA	Creation date 2024-09-23	Language en	Page 2/2