

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2282B

SIMOTICS SD - 280 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	90.00	-/-	159.00	1486	580.0	94.2	94.3	93.6	0.87	0.84	0.75	7.3	2.6	3.1	IE2
690	Y	50	90.00	-/-	92.00	1486	580.0	94.2	94.3	93.6	0.87	0.84	0.75	7.3	2.6	3.1	IE2
460	Δ	60	104.00	-/-	158.00	1785	560.0	95.0	95.1	94.3	0.87	0.85	0.77	7.2	2.5	3.1	IE2
460	Δ	60	90.00	-/-	137.00	1788	480.0	94.5	94.3	93.3	0.87	0.84	0.75	8.1	2.9	3.4	IE2
IM B3 / IM 1001			FS 280 M			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 20.3 s 35.5 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	71 / 85 dB(A) ^{2) 3)}	78 / 92 dB(A) ^{2) 3)}	External earthing terminal	Yes (standard)
Moment of inertia	1.4000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE NDE	30 g 30 g	8000 h	Net weight of the motor (IM B3)	570 kg
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1501-2DB23-4AA4-Z				
© Siemens AG 2022	d22				rev.
					01
					creation date
					2022-07-05
					language
					en
					Page
					1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2282B

SIMOTICS SD - 280 M - IM B3 - 4p

Special design

D22 Motor without CE character for export outside the EEA (see EU regulation 2019/1781)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1501-2DB23-4AA4-Z D22				document number
© Siemens AG 2022				rev. 01	creation date 2022-07-05
				language en	Page 2/2

