

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2314A

SIMOTICS SD - 315 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
IM B3 / IM 1001			FS 315 L		930 kg		IP55				IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 36.9 s 64.4 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	80.0 / 95.0 dB(A) ²⁾	84.0 / 99.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.8000 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 316	6316 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g 3000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1501-3AA49-0AB4-Z L22+M1Y			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-22 21:06	language en	Page 1/2	

SIMOTICS SD - 315 L - IM B3 - 2p

Special design

L22	Bearing design for increased cantilever forces	M1Y	Non-standard winding:
-----	--	-----	-----------------------

Notes:

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

customer

language	Page
en	2/2