

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2314B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_k/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
380	Δ	50	160.00	-/-	295.00	1490	1030.0	94.9	95.0	94.5	0.87	0.84	0.77	7.2	2.8	3.1	IE2
660	Y	50	160.00	-/-	170.00	1490	1030.0	94.9	95.0	94.5	0.87	0.84	0.77	7.2	2.8	3.1	IE2
440	Δ	60	184.00	-/-	290.00	1788	980.0	95.4	95.4	94.6	0.88	0.86	0.79	7.2	2.9	3.0	IE2
440	Δ	60	160.00	-/-	255.00	1790	850.0	95.0	94.7	93.5	0.87	0.83	0.75	8.3	3.1	3.2	IE2

IM B3 / IM 1001	FS 315 L	940 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	----------	--------	------	--------------	------------------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 23.2 s | 39.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	76.0 / 91.0 dB(A) ²⁾	80.0 / 95.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	2.8000 kg m ²		Vibration severity grade	B
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(J) 6 resistance thermometers PT100 (12 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_k/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_d/M_N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

	document type datasheet	document status released	customer	
	title 1LE1501-3AB43-3AJ4-Z B02+H07+L00+M11+Q02	document number	rev. 01	creation date 2021-04-23 16:15
© Siemens AG 2021				Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2314B

SIMOTICS SD - 315 L - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	M11	Stainless steel rating plate
H07	Stainless steel screws and bolts (outside the motor)	Q02	Anti-condensation heating for 230 V (2 terminals)
L00	Vibration severity level B		

Additional information:

Space heaters

Technical data: 1-phase, 230 V 109W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

SIEMENS	document type datasheet	document status released	customer			
	title 1LE1501-3AB43-3AJ4-Z B02+H07+L00+M11+Q02	document number	rev. 01	creation date 2021-04-23 16:15	language en	Page 2/2
© Siemens AG 2021						