

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2314B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	50	153.60	-/-	270.00	1490	984.5	94.9	94.9	94.3	0.87	0.83	0.76	7.5	2.9	3.2	IE2
690	Y	50	153.60	-/-	157.00	1490	984.5	94.9	94.9	94.3	0.87	0.83	0.76	7.5	2.9	3.2	IE2
460	Δ	60	176.64	-/-	265.00	1785	945.0	95.4	95.3	94.3	0.88	0.85	0.78	7.5	3.0	3.1	IE2
460	Δ	60	160.00	-/-	245.00	1790	850.0	95.0	94.7	93.5	0.87	0.83	0.75	8.3	3.1	3.2	IE2
IM B3 / IM 1001		FS 315 L		940 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +45 °C / 1,000 m

Locked rotor time (hot / cold) : 23.2 s | 39.1 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	76.0 / 91.0 dB(A) ²⁾	80.0 / 95.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	2.8000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 3000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
© Siemens AG 2021	title			document number			
	1LE1501-3AB43-4AB4-Z B02+N05+Q02+S03						
				rev.	creation date	language	Page
				01	2021-04-21 18:33	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2314B

SIMOTICS SD - 315 L - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Q02	Anti-condensation heating for 230 V (2 terminals)
N05	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 45°C, power reduced	S03	Special paint finish in sea air resistant C4

Additional information:

Space heaters

Technical data: 1-phase, 230 V 109W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1501-3AB43-4AB4-Z							
© Siemens AG 2021	B02+N05+Q02+S03	rev. 01	creation date 2021-04-21 18:33		language en	Page 2/2		