

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2315B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	200.00	-/-	350.00	1490	1280.0	95.1	95.3	94.7	0.87	0.84	0.75	7.5	3.1	3.2	IE2
690	Y	50	200.00	-/-	200.00	1490	1280.0	95.1	95.3	94.7	0.87	0.84	0.75	7.5	3.1	3.2	IE2
460	Δ	60	230.00	-/-	350.00	1790	1230.0	95.4	95.5	94.9	0.87	0.86	0.77	7.7	3.4	3.1	IE2
460	Δ	60	200.00	-/-	305.00	1792	1070.0	95.4	94.7	93.6	0.86	0.82	0.72	9.0	3.8	3.2	IE2
IM B3 / IM 1001		FS 315 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 25 s 41.6 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	77 / 92 dB(A) ^{2) 3)}	84 / 98 dB(A) ^{2) 3)}	External earthing terminal	Yes (standard)
Moment of inertia	3.5000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	1140 kg
Regreasing device	Yes (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5
Contact screw thread	M12	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
M_B/M_N = break down torque / nominal torque

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet			document status released	
	title 1LE1501-3AB53-4AA4-Z D22			document number	
© Siemens AG 2022			rev. 01	creation date 2022-08-19	language en
					Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2315B

SIMOTICS SD - 315 L - IM B3 - 4p

Special design

D22 Motor without CE character for export outside the EEA (see EU regulation 2019/1781)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1501-3AB53-4AA4-Z D22				document number
© Siemens AG 2022		rev. 01	creation date 2022-08-19	language en	Page 2/2

